


100m USB 3.2 HDBaseT  
Extender with PoH+  
EX-100-USB3

EX-100-USB3 (Front)



EX-100-USB3 (Rear)



<b>A</b> Power LED	<b>Solid:</b> The unit is powered On <b>Off:</b> The unit is powered Off
<b>B</b> Link LED	<b>On:</b> Indicates link with receiving device <b>Off:</b> No link with receiver/powered off
<b>C</b> USB LED	<b>On:</b> USB data transmission <b>Off:</b> No USB data transmission
<b>D</b> DC 20V	Connect to the 20V power adapter
<b>E</b> USB Host	USB 3.0 Type B female Connection of USB Host device
<b>F</b> Link LED	<b>On:</b> Indicates link with receiving device <b>Off:</b> No link with receiver/powered off
<b>G</b> USB3 Link	Connect to the receiver for USB transmission
<b>H</b> USB LED	<b>On:</b> USB data transmission <b>Off:</b> No USB data transmission
<b>I</b> Update Port	Micro USB for firmware updates

<b>A</b> Power LED	<b>Solid:</b> The unit is powered On <b>Off:</b> The unit is powered Off
<b>B</b> USB Device	USB 1 Type A female Connection of USB peripherals
<b>C</b> DC 20V	Connect to the 20V power adapter
<b>D</b> Link LED	<b>On:</b> Indicates link with receiving device <b>Off:</b> No link with receiver/powered off
<b>E</b> USB3 Link	Connect to the receiver for USB transmission
<b>F</b> USB LED	<b>On:</b> USB data transmission <b>Off:</b> No USB data transmission

# WyreStorm - Powerful. Reliable. Simple.

## Introduction

A versatile and powerful solution for extending your USB connectivity. Engineered to support the latest USB 3.2 Gen 1 standard, this extender offers rapid data transfer speeds of up to 5Gbps, ideal for a variety of high-performance USB peripherals. Its four-port design allows for simultaneous connection of multiple devices. With a remarkable capability to extend USB signals up to 100 meters, it ensures reliable, long-distance connectivity.

## Key Features

- 4 Port Design
- USB 3.0 (5Gbps)
- 100m Extension
- PoH+

## In the Box

- 1x EX-100-USB3
- 1x DC 20V 3A Power Supply (US/EU/UK/AU)
- 1x 1.8m USB 3.0 Type-A to Type-B Cable (5Gb)
- 4x Mounting Bracket
- 1x Quickstart Guide

## Specifications

<b>Audio and Video</b>	
<b>Inputs</b>	<b>TX:</b> 1x USB Host <b>RX:</b> 4x USB 3.2 Type A1 x RJ45 Input
<b>Outputs</b>	<b>TX:</b> 1x RJ45 Female
<b>Supported Standards</b>	USB 3.2 Gen 1
<b>Power</b>	
<b>Power Supply</b>	DC 20V 3A with locking connector
<b>Max. Power Consumption</b>	39.79W (USB fully-loaded) 6.94W (No USB load)
<b>Environmental</b>	
<b>Operating Temperature</b>	0 to + 45°C (32 to + 113 °F), 10% to 90%, non-condensing
<b>Storage Temperature</b>	-20 to +70°C (-4 to + 158 °F), 10% to 90%, non-condensing
<b>Dimensions and Weight</b>	
<b>Height</b>	20.5mm/0.8in
<b>Width</b>	150mm/5.9in
<b>Depth</b>	100mm/3.93in
<b>Regulatory</b>	
<b>Safety and Emission</b>	CE   FCC   RoHS   RCM   EAC   UKCA

**Note:** WyreStorm reserves the right to change product specification, appearance or dimensions of this product at any time without prior notice.

## Warranty Information

WyreStorm Technologies ProAV Corporation warrants that its products to be free from defects in material and workmanship under normal use for a period of five (5) years from the date of purchase. Refer to the Product Warranty page on [wyrestorm.com](http://wyrestorm.com) for more details on our limited product warranty.

